

Extractability™

PRODUCT INFORMATION

Protecto Advanced Bench

SUMMARY

ProtectoBench is a self-contained cross-draught extraction bench with a durable large surface area filter cartridge. It comes complete with a filter full alarm and optional manual and auto cleaning functions. The machine boasts an expandable working area

The ProtectoBench is an extraction and filter system in one. It's feature rich with built in LED Lighting, 2 x 240v power sockets and a compressed air outlet.

TARGET APPLICATIONS

Welding and grinding alloyed and unalloyed steels, precious metals, galvanised material.

Not to be used on explosive dusts



FURTHER INFORMATION

The unit is capable of handling up to 5,850 m³/hr over a work surface area of 660mm x 1200mm. The unit has a 4kw 3ph 415v and is supplied with mains sockets for power tools. The unit filters welding fumes and grinding dust before recirculating the cleaned air back into the workplace. The filters are in turn cleaned manually with compressed air which blows the particulates into a collection tray ready for disposal. There are two options available for filters, the standard filter is a Nano Blend FR 40m² F9 Class with the optional PolyMIGHT PTFE 65 30m² H14 Class
Noise Level without silencer is 81dB with silencer is 73dB

ARTICLES & ACCESSORIES

Part Number	Product Description
EXT562110140	PROTECTOBENCH ADVANCED H13
EXT562110140NANO	Replacement Cartridge Standard/Nano 20 m2
EXT562110140PTFE	Replacement Cartridge PTFE 15 m2

TECHNICAL SPECIFICATION

Extraction Capacity	5850 m³/h
Filter Efficiency	> 99%
Motor Power	4kW
Noise Level (nozzle installed)	73 dB(A)
Weight	255 kg
Dimensions (LxWxH)	1260mm x 1500mm x 1600mm Total

For further information, contact Extractability technical support on **0845 862 2620** or email service@extractability.eu