## DING BLAN



#### CREPIM

ERPPIM

F per Actions Simplifies - 792 178 816 R.C.S. ARRAS

GIN! Perc de le Porte Nord - rue Christophe Colomit
62700 BRUAY LA BUISSERE France

Tel: 09 21.61.64.00 Fee: 09.21.61.64.01 E-mail: contect@crepim.fr www.crepim.fr SIRET 792 378 816 00015 / APE 71128 / T.V.A. FR85 792 178 816

#### 4.2 Classement / Classification

Le produit, Couverture de soudage CEPRO HERCULES, en fonction de son comportement au feu, est classé / The product, CEPRO Welding Blanket HERCULES, based on its reaction to fire behavior, is classified: A2.

Le classement complémentaire en relation avec la production de fumée est / Complementary classification in relation to smoke production is: \$1.

Le classement complémentaire en relation avec les gouttelettes/particules enflammées est / Complementary classification in relation to fall of flaming droplets/particles is: d0.

Le format du classement de réaction au feu pour les produits de construction, à l'exception des revêtements de sol et des produits d'isolation thermique pour conduites linéaires est / The format of the reaction to fire classification for construction products excluding flooring and linear pipe thermal insulation products is:

Comportement au feu Fire behaviour		Production de fumée Smoke production			Gouttelettes enflammées Flaming droplets	
A2	-	s	1	,	d	0

Autrement dit / In other words, A2 - s1, d0

Classement de réaction au feu / Reaction to fire classification:

A2-s1,d0

#### 4.3 Champ d'application / Field of application:

Le présent classement est valable pour les paramètres suivants liés au produit / The classification is valid for the following product parameters:

Composition: Aucune variation autorisée / No variation allowed

Epaisseur / Thickness: 1.6 mm

Masse surfacique / Surface density: 1.22 kg/m2

Masse volumique / Density: 762.5 kg/m3

Faces identiques / Identical faces Face exposée / Exposed face :

Couleur / Color: Gris / Grev

Pour déciater, ou non, la conformité à la spécification, il ri's pas été tenu explicitement compte de l'incentitude associée au résultat Whether or not lo declare compliance with the appointation, the uncentainty associated with the result was not explicitly faken into accou Lair reproduction de ce rapport dessa in els stantrisée que sous sa forme intégrale. Reproduction of this test report is only permitted in as full form.

Le CREPPM ne peut être tenu responsable des informations relatives à l'élément testé. Ces informations sont fournies par le demandeur CREPPM cannot be real responsable for information relatives à l'élément monté. This information is provided by the applicant.

2EN

PFS Weldingblankets Premium Hercules

CEPRO

Product description Glass fibre material

Manufacturer / Supplier Cepro International BV Date of issue February 2014

P.O. Box 183 5120 AD Rijen The Netherlands

Tel. no. for information / emergency +31 (0)161 22 64 72 Fax no. for information / emergency +31 (0)161 22 49 73

2. HAZARD INFORMATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Not determined

Classification according to Regulation 67/548/EEC or 1999/45/EC

No classification

**Label elements**The product does not require a hazard warning label in accordance with

EC-directives. This product is an article and therefore it does not require

labelling according to EC directives/GefStoffV.

Other hazards

**Physico-chemical hazards** no particular hazards known. **Environmental hazards** no particular hazards known.

Other hazards none

3. COMPOSITION / INFORMATION ON INGREDIENTS

Range [%] Substance 85-100 glass

CAS:65997-17-3, EINECS/ELINCS: 266-046-0

Comment on component parts No dangerous components.

Substances of Very High Concern - SVHC: substances are not contained or

are below 0,1 %.

4. FIRST AID MEASURES

**Description of first aid measures** 

**General information** Change soaked clothing.

**Inhalation** Ensure supply of fresh air. In the event of symptoms refer for medical treatment.

**Skin contact** When in contact with the skin, clean with soap and water. Consult a doctor if skin

irritation persists.

**Eye contact** In case of contact with eyes rinse thoroughly with plenty of water and seek medical

advice.

**Ingestion** Not applicable

Most important symptoms and effects, both acute and delayed

No information available

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

Forward this sheet to the doctor.

Version 004 - Check our website for the latest version.

**SEPRO\_PFS\_Weldingblankets\_Premium\_Hercules\_2EN** 



# **HERCULES WELDING BLANKET**



#### **5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media Product itself is non-combustible. Fire extinguishing method of

surrounding areas must be considered.

**Extinguishing media that** 

must not be used

None.

Special hazards arising from the substance or mixture

Unknown risk of formation of toxic pyrolysis products.

Advice for fire-fighters not applicable

Fire residues and contaminated fire-fighting water must be disposed of

in accordance with the local regulations.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Use breathing apparatus if exposed to dust.

**Environmental precautions** Not applicable

Methods and material for containment cleaning up

Dispose of absorbed material in accordance with the regulations. Take up

mechanically.

Reference to other sections See section 8+13

#### 7. HANDLING AND STORAGE

Precautions for safe handling With mechanical processing however fibers can be set free.

Avoid the formation and depositions of dust.

Provide vacuuming if dust raised.

Dust deposits that cannot be avoided must be taken up regularly.

Wash hands before breaks and after work.

Use barrier skin cream

take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

No special measures necessary. See product use. section 12

#### 8. EXPOSURE CONTROL / PERSONAL PROTECTION

**Control parameters** 

Specific end use(s)

Ingredients with occupational exposure limits to be monitored (GB)

Range [%] Substance 85-100 glass

CAS: 65997-17-3, EINECS/ELINCS: 266-046-0

Long-term exposure: TLV-TWA: 1 f/cc (respirable): 5 mg/m³ (inhalable (ACGHIH

**Exposure controls** 

Additional advice on system design

Ensure adequate ventilation on workstation

To pay attention to dust limit value (ACGHI-2011: 10 mg/m³ particle inhalable;

3 mg/m³ particle respirable).

**Eye protection** Safety glasses

**Hand protection** The details concerned are recommendations. Please contact the glove supplier

for further information. Leather (EN 388).

**Skin protection** Long-sleeved work clothes.



### **HERCULES WELDING BLANKET**



Other Avoid contact with eyes and skin.

Do not inhale dust.

Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be

ascertained with the respective supplier.

**Respiratory protection:** Breathing apparatus in the event of high concentrations.

Short term: filter apparatus, filter P2.

Thermal hazards No information available

Delimitation and monitoring of the environmental exposition:

not determined

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form** Solid in different forms. Vapour pressure (kPa) Not applicable. Colour Various. Not determinated. Density (g/m) Odourless. Odour Bulk density (kg/m³) Not applicable. Not applicable. Solubility in water Immiscible. pH-value Partition coefficient: pH-value, 1 % Not applicable. Not applicable.

n-octanol / water

Boiling point (°C) Not applicable. Viscosity Not applicable. Flash point (°C) Not applicable. Relative vapour density Not applicable.

determined in air

Flammability (°C) Not applicable. Evaporation speed Not applicable.

Lower explosion limit Not applicable. Melting point (°C) Not determinated.

Upper explosion limit Not applicable. Autoignition temp. (°C) Not applicable.

Combustible properties No. Decomposition temp. (°C) Not applicable.

Other information No information available

#### **10. STABILITY AND REACTIVITY**

**Reactivity** No hazardous reactions known

Chemical stability Stable under normal ambient conditions (ambient temperature)

Possibility of hazardous reactions

No hazardous reactions known

Conditions to avoid No information available Incompatible materials No information available

Hazardous decompostions products

#### 11. TOXICOLOGICAL INFORMATION

not determined Acute oral toxicity: Acute dermal toxicity: not determined Acute inhalational toxicity: not determined Irritant effect on eye: not determined Irritant effect on skin: not determined Sensitization: not determined not determined Subacute toxicity: Chronic toxicity: not determined Mutagenicity: not determined Reproduction toxicity: not determined Carcinogenicity: not determined

Experiences made in practice: Contains fibres with diameter > 6 micrometers. The filament is not breathable

(WHO).

Fiber abrasion can cause mechanical skin irritation.

**General remarks:** No classification on the basis of the calculation procedure of the preparation

directive.

## **HERCULES WELDING BLANKET**



#### 12. ECOLOGICAL INFORMATION

**Toxicity** 

Persistence and degradability

Behaviour in environment compartments

not applicable

Behaviour in sewage plant

not applicable

Biological degradability

not applicable

Bioaccumulative potential

No information available

Mobility in soil

No information available

Results of PBT and vPvB assessment

No information available

Otherwise adverse effects

The product is insoluble in water.

Can be separated out mechanically in purifications plants.

#### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. it is not possible to determine a waste code for this product in accordance with the European Wast Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

**Product** 

Coordinate disposal with the authorities if necessary.

Waste no. (recommended)

101112 101103

Contaminated packaging

Uncontaminated packaging may be taken for recycling

Waste no. (recommended)

150101 150102

### 14. TRANSPORT INFORMATION

**UN number** see section 14 in accordance with UN shipping name

UN proper shipping name

Transport by land according NO DANGEROUS GOODS

to ADR/RID

Inland navigation (ADN) NO DANGEROUS GOODS Marine transport in accordance NO DANGEROUS GOODS

with IMDG

Air transport in accordance NO DANGEROUS GOODS

with IMDG

**Transport hazard class(es) Packing group Environmental hazards**see section 14 in accordance with UN shipping name see section 14 in accordance with UN shipping name see section 14 in accordance with UN shipping name

Special precautions for user relevant information under section 6 to 8

Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

not applicable



# **HERCULES WELDING BLANKET**



#### **15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

**EEC-REGULATIONS:** 1967/548 (2008/58, 30. ATP/ 31. ATP); 1991/689 (2001/118); 1999/13; 2004/42;

648/2004; 1907/2006 (Reach); 1272/2008; 75/324/EWG (2008/47/EG

**TRANSPORT-REGULATIONS:** DOT-Classification, ADR (2009); IMDG-Code (34. Amdt.); IATA-DGR (2010).

NATIONAL REGULATIONS (GB) EH40/2005 Workplace exposure limits with amendments October 2007.

CHIP 3/ CHIP 4

Observe employment restrictions for people

Not applicable

OC (1999/13/CE) Not applicable

Chemical safety assessment Chemical safety assessments for substances in this mixture were not carried

out

#### **16. OTHER INFORMATION**

#### Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

Route

RID = Règlement concernant le transport international ferroviaire de marchandises

dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par

voie de navigation intérieure

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

Customs tariff Not determined

Disclaimer: This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# HERCULES WELDING BLANKET



### TECHNICAL DATA

Test			Standard*
1. Weave		Plain	DIN 61 101 - 1
2. Width		1000 mm	DIN EN 1773
3. Thickness		1,6 mm	DIN EN ISO 2286-3
4. Weight		1220 g/m²	DIN EN ISO 12127
5. Number of threads	warp	5,0 threads/cm	DIN EN 1049 - 2
	weft	3,0 threads/cm	
6. Yarn count	warp	1250 tex	DIN EN ISO 2060
	weft	1250 tex	
7. Filament diameter	warp	9 μm	DIN 53 811
	weft	9 μm	
8. Tensile strength	warp	> 6000 N/5 cm	ISO 4606
	weft	> 3200 N/5 cm	

<sup>\*</sup> partly according to the standard

Subject to tolerances

CEPRO\_PFS\_Weldingblankets\_Premium\_Hercules\_2EN