

PRODUCT INFORMATION

HOSE TAILS

DA2001414

DESCRIPTION

A hose tail is used with a hose nut to attach a gas hose to a connection on a item of gas equipment (e.g. regulators, shanks and cutters). Available for a variety of hose bore sizes. Use with hose nuts and 'o' clips on high compression fittings to secure in place and seal.



FURTHER INFORMATION

The tail passes through the nut and the hose is secured onto it, the nut is then tightened onto the relevant equipment connection.

Weldability stock hose tails in three configurations, to suit popular hose bore sizes and standard hose nut dimensions. 1/4" hose tails are usually used with 6mm gas hose. 5/16" tails are used with 8mm hose. 3/8" tails are usually used with 10mm gas hose. The 3/16" hose tail size is used with a 5mm gas hose.

1/4" BSP hose nuts are suitable for connecting hoses to lightweight style shanks, whereas 3/8" BSP nuts are used to connect to regulators, Type 3, 4 and 5 style shanks and NM type cutters.

NOTES

Weldability stock a complete range of gas equipment, which feature many hose attachments. These attachments include hose nuts (DA10014LH – DA10038RH), splicers (DA30014 – DA30056), hose couplers (DA4001414LH – DA4003838RH), hose check valves (DA5001414LH – DA5003856RH) and adaptors (DA6003814BLH – DA6003814SRH).

All are manufactured to high levels of quality to help ensure a leak-proof gas line.

ARTICLES & ACCESSORIES

Part Number	Product Description
DA2001414	1/4 HOSE TAIL (1/4 NUT)
DA2003814	1/4 HOSE TAIL (3/8 NUT)
DA2003814B	HOSE TAIL 3/8 NUT
DA2003836	3/16 HOSE TAIL (3/8 NUT)
DA2003838	3/8 HOSE TAIL (3/8 NUT)
DA2003856	5/16 HOSE TAIL (3/8 NUT)

TECHNICAL INFORMATION

All measurements are to BSP imperial standards.

For further information, contact Weldability | Sif technical support on **0870 330 7757** or email service@weldability-sif.com



Registered in England No. 1684362
Registered Office: as above

Doc Ref: WELDABILITY/PI/DA2001414