

PRODUCT INFORMATION

CERAMIGUARD DRY-FILM SPRAY

EG5001

SUMMARY

Our ceramic particulate spatter-prevention spray-coating, designed to extend the life of contact tips and shrouds in industrial semi-automated and robotic MIG welding applications, including heavy equipment fabrication and vehicle production.

CeraMIGuard out-performs regular anti-spatter sprays and increases productivity, reducing downtime by minimising tip and shroud changes.



TARGET APPLICATIONS

Sif CeraMIGuard is Ideal for:

- Protection of tips and shrouds in industrial MIG fabrications.
- Can also be applied to jigs, fixtures & cables to protect them from spatter adhesion.

FURTHER INFORMATION

Typically, CeraMIGuard-coated shrouds last over twice as long as uncoated shrouds before spatter build-up adversely affects welding performance. In many applications, only a single application of CeraMIGuard is required per shift, which removes the needs for reaming stations and tip-dip.

The spray can also be applied to jigs, fixtures and power cables to protect them from spatter damage. It can be removed by rubbing with a warm, damp cloth.

ARTICLES & ACCESSORIES

Part Number	Product Description
EG5001	CeraMIGuard Dry-Film Spray

TECHNICAL SPECIFICATION

Form	Aerosol
Solubility	Slightly miscible in water
Colour	White
Odour	Characteristic

For further information, contact Weldability | Sif technical support on **0870 330 7757** or email **service@weldability-sif.com**