

PRODUCT INFORMATION

HOSE COUPLERS

DESCRIPTION

A hose coupler is used in association with two hose nuts and two hose tails to join two pieces of hose together.

FURTHER INFORMATION

Weldability stock couplers to take combinations of 3/8" and 1/4" hose nuts, which can be used in accordance with the appropriate hose tails for the size of the hoses to be connected.

Right-hand threaded nuts and couplers are typically used in oxygen and argon connections, whereas left-hand threaded nuts and couplers, bearing the universal indicator notches, are used with acetylene and propane connections.



DA4001414LH

NOTES

Weldability stock a complete range of gas equipment, which features many hose attachments. These attachments include hose tails (DA2001414 – DA2003856), splicers (DA30014 – DA30056), hose couplers (DA4001414LH – DA4003838RH), hose check valves (DA5001414LH – DA5003856RH) and adaptors (DA6003814BLH – DA6003814SRH).

All are manufactured to high levels of quality to help ensure a leak-proof gas line.

ARTICLES & ACCESSORIES

Part Number	Product Description
DA4001414LH	1/4" – 1/4" HOSE COUPLER LH
DA4001414RH	1/4" – 1/4" HOSE COUPLER RH
DA4003814LH	3/8" – 1/4" HOSE COUPLER LH
DA4003814RH	3/8" – 1/4" HOSE COUPLER RH
DA4003838LH	3/8" – 3/8" HOSE COUPLER LH
DA4003838RH	3/8" – 3/8" HOSE COUPLER RH

TECHNICAL INFORMATION

All measurements are to BSP imperial standards.

For further information, contact Weldability | Sif technical support on **0870 330 7757** or email service@weldability-sif.com



Registered in England No. 1684362
Registered Office: as above

Doc Ref: WELDABILITY/PI/DA4001414LH