

PRODUCT INFORMATION

FLAWTEK DETECTION SYSTEM

DESCRIPTION

When used in sequence, the three-part Flawtek system exposes cracks and flaws in a finished weld in just 10-20 minutes.



EG2001

INFORMATION

The three-stage process consists of the Cleaner (EG2001), a Penetrant (EG2002) and a Developer (EG2003). The cleaner removes residue, the penetrant seeps in to any cracks in the weld and the developer turns the penetrant pink, clearly drawing attention to any problem areas.

Each are sold separately under the relevant part number. To be used in sequence to locate any cracks in a weld. If the weld is weak the penetrant will seep through and the developer will turn the liquid pink to highlight problem areas swiftly to improve efficiency.

Use in sequence and leave for 10 to 20 minutes for best results.

ARTICLES & ACCESSORIES

Part Number	Product Description
EG2001	FLAWTEK CLEANER (400MLS)
EG2002	FLAWTEK PENETRANT (400MLS)
EG2003	FLAWTEK DEVELOPER (370MLS)

TECHNICAL INFORMATION

Pressurised container – should not be exposed to intense heat or flame.

Material safety data regarding this product is available on request from Weldability Sif.

For further information, contact Weldability | Sif technical support on **0870 330 7757** or email service@weldability-sif.com



Registered in England No. 1684362
Registered Office: as above

Doc Ref: SIF/PI/EG2001